

Mobility

Innovative Design

- Light weight around 7.5Kg (16.5lbs)
- Wide-viewing angle 15"LED (0° 30° tilted)
- · Removable battery, 120 minutes in active mode
- Dual transducer ports (Built-in)
- Probe holders
- · Ports: USB, LAN, VGA, DVI, Video, Remote
- Ergonomic trolley (accessory box, printer socket & probe holders, optional: theft-proof lock)
- Short-cut key function
- Multi-language



Clinical Versatility

A complete solution for ultrasound diagnosis

- Cardiovascular
- Radiology
- Internal Medicine
- Small Parts
- General Imaging

- Vascular
- Intensive Care
- Emergency
- MSK
- Point of Care



Advanced **Technologi**

FHI

- FHI is an innovative harmonic imaging technology that uses multiple transmission and receiving methods based on the patient's size and weight. This allows the EBit 60 to maintain image resolution when imaging larger patients.
- Traditional Tissue Harmonics and Phased Harmonics compromise image quality and resolution when penetration is increased.
- Chison's FHI technology greatly improves diagnostic abilities and clinical confidence in larger, difficult-to-image patients.



FHI OFF

FHI ON

Q-flow

- This adaptive color detection technology can automatically adjust the assessment of color signal and noise according to different tissues.
- As a result, color sensitivity of low-velocity flow is significantly enhanced.




Q-Flow OFF

Q-Flow ON



- for ultrasound signal receiving.
- Doubles the volume of signals received over traditional methods, increasing image resolution and generating more accurate images.
- Produces higher frame rates, ensuring better diagnostic confidence and efficiency, especially for moving organs.



X-contrast

- The EBit 60 allows one-touch user-adjusted contrast resolution based upon differences in tissue density.
- Enhance, Normal, and Suppress settings increase or decrease contrast resolution, based on the tissue type and user preference.



Enhance


Normal

Suppress


Diagnostic Confidence




Aorta valve regultation, CW Mode




TDI, PW Mode




LV Long Axis, Free M Mode




Apical Four Chambers, Color M Mode




Cardiac, 4B Mode




AUTO IMT



Superficial Vessel< 1cm depth, C Mode



Popliteal Artery, Triplex Mode




Carotid Plaque, B Mode









Uterus, B Mode Liver, B Mode Fetal Heart, B Mode









Superficial Vessel< 0.2cm depth, CPA Mode

Kidney, C Mode Aorta Artery, C Mode







Primary flexor tendon , 2B Mode

Thyroid multiple adenomas, B/BC Mode

Umbillical Cord, B/BC Mode





2.0 - 6.8 MHz Convex C3-E



4.0 - 15.0 MHz Linear L7-E



7.0 - 18.0 MHz(With FHI) Linear L12-E



4.0 - 15.0 MHz Linear L7W-E



1.5 - 5.3 MHz Phased Array P3-E



2.0 - 8.0 MHz Phased Array P6-E



4.0 - 12.0 MHz Transvaginal V6-E



4.0 - 15.0 MHz Transvaginal V7-E



4.0 - 15.0 MHz Trans-Rectal L7R-E



2.0 - 6.8 MHz Micro-Convex MC3-E Micro-Convex MC6-E



4.0 - 12.0 MHz



4.0 - 10.7 MHz Micro-Convex MC5-E

CHISON Medical Technologies Co., Ltd

Sales & Service Contact Address:

No.9, Xinhuihuan Road, Xinwu District, Wuxi, Jiangsu, China 214028

TEL: 0086-510-85310593 / 85310937 FAX: 0086-510-85310726 EMAIL: export@chison.com.cn